

GENERAL CONDITIONS:

1. It is the applicants responsibility to advise the County when all work on the road allowance is completed and ready for inspection. Costs for repeated inspections may be deducted from the deposit. The County reserves the right to retain all or part of the deposit to offset County costs to restore unsatisfactory work to match original conditions, for any damage claims, or for other County costs related to work performed under this permit. The County also reserves the right to retain all or part of the deposit for a minimum period of six months after initial acceptance by the County for potential settlements, ground cover restoration, etc.
2. The applicant is required to protect existing cables, conduits, structures or other appurtenances from damage as result of the work under this permit. Any such damage occurring shall be immediately repaired to the satisfaction of the authority having jurisdiction over the damaged plant.
3. The County does not guarantee that the location selected for services is not in use by other utilities or services.
4. The applicant agrees that prior to beginning any work on the road allowance, proper signing and barricades shall be provided for traffic control in conformance with the "Traffic Control Manual for Roadway Work Operations" - latest edition.

We, the undersigned applicants, agree and bind ourselves to indemnify and save harmless the County of Middlesex from any and all claims arising as result of the work for which this Permit is issued.

_____ **Date of Application**

_____ **Signature of Applicant**

Authorization is hereby granted to the applicant and/or his agents to perform the above described work subject to the General Conditions named in the Application and subject to the following additional specific conditions. By beginning the work on the road allowance, the Applicant(s) agree and bind themselves to ALL conditions on this Permit.

SPECIAL CONDITIONS (check below):

Road Crossings are to be **BORED**. Pavement must not be cut. Bore pits to be located outside of the shoulder area a minimum of 3 metres from the edge of pavement. Compaction of backfills shall be 95% Standard Proctor. All disturbed areas must be restored to original conditions including the necessary sodding or seeding. Disturbed sidewalks and curb and gutter shall be replaced.

Compaction of backfills shall be 95% Standard Proctor. All disturbed areas must be restored to original conditions including the necessary sodding or seeding. Disturbed sidewalks and curb and gutter shall be replaced.

USE SEPARATE SHEET FOR FURTHER CONDITIONS

DATE: _____

Per: _____
Engineering Supervisor or County Engineer

Distribution: Applicant ___ **File** ___ **District Foreman #**